



Quality is Behind the Diamond®

## Amerex Corporation

Manufactured to  
ANSI / UL Standards  
AS & NZ Standards  
ISO-9001 / ISO-14001 Certified

### RUGGED

- Fully Drawn dependable Steel Cylinders
- No Weld Construction
- All Metal Valve Construction
- UV Rated Powder Coating
- Easy to Service and Maintain
- UL Listed
- Coast Guard Approved
- Temperature Range -53°C to 50°C
- Bar Coded Labels

## STORED PRESSURE

### ALUMINIUM VALVE RANGE



### BRASS VALVE RANGE



**BE Dry Chemical Extinguishers** contain a siliconized sodium bicarbonate based dry chemical powder with free flowing and non-caking additives. Economical Class B & E protection with lower initial cost and recharging. This chemical smothers fires in flammable liquids and pressurized gas and will not conduct electricity back to the

Specifications	Aluminium					Brass Chrome Plated (No Alloy)		
Valve Type	Aluminium					Brass Chrome Plated (No Alloy)		
Model	B403T	B409TAS	B453AS	B457AS	B412AS	B462	B447	408AS
Size & Capacity	1.0kg	2.3kg	2.3kg	4.5kg	9.0kg	2.3kg	4.5kg	9.0kg
Application	Nozzle		Hose & Nozzle			Hose & Nozzle		
AS/NZ Rating	-	30B:E	-	40B:E	80B:E	-	-	80B:E
U.L. Rating	10B:C	10B:C	40B:C	60B:C	120B:C	40B:C	60B:C	120B:C
F.M. Approved	Yes	Yes		Yes	Yes	Yes	Yes	Yes
Shipping Wt. Kg.	2.26	4.2	4.3	8.2	17.2	6.2	8.6	17.7
Height mm	294	387	387	508	591	413	521	607
Width mm	146	140	184	186	260	216	222	260
Depth mm	76	108	108	127	178	108	108	178
Range m	3 - 5	4 - 6	4 - 6	5 - 7	5 - 7	4 - 6	5 - 7	5 - 7
Disch. Time Sec	10	10	14	18	28	14	18	28
Chrome Plated Cyl.	Yes	Yes	Yes					
Corrosion Paint								
Std Bracket			Wall Bracket			Wall Bracket		

For more information contact :

**FIRE SAFETY EQUIPMENT**

[www.fsequip.com.au](http://www.fsequip.com.au)

Sydney - Brisbane - Auckland



BE DRY CHEMICAL