



Quality is Behind the Diamond®

**Amerex Corporation**

Manufactured to  
ANSI / UL Standards  
AS & NZ Standards  
ISO-9001 / ISO-14001 Certified

**RUGGED**

- 6 Year Warranty
- Dependable Drawn Steel Cylinders
- All Metal Valve Construction
- Special corrosion resistant yellow
- Class D color coded paint finish
- Temperature Range -40°F to 120°F



CLASS D

The Amerex “soft flow” extension applicator is particularly suited for fighting Class D fires. It allows the operator to stand away from the extreme heat and toxic fumes caused by burning material. The easily controlled, even discharge provides a non-dispersing application of the agent. The extension applicator may be quickly detached to provide a straight stream of chemical where greater range is required.

**MODEL B570** contains a special blended Sodium Chloride based dry powder extinguishing agent. Heat from the fire causes it to cake and form a crust excluding air and dissipating heat from burning metal. Metal fires involving magnesium, sodium, potassium and sodium-potassium alloys can be successfully extinguished with this extinguisher. There is data showing that zirconium, uranium, titanium, and powdered aluminum fires can be controlled and extinguished with this unique extinguisher.

**Extinguishing Capacity**

- Magnesium Chips: 4 ft2 and/or 6 lbs. of metal
- Sodium or Potassium Spill: 5 ft2 and/or 5 lbs.of metal
- Sodium or Potassium Spill Depth Over 1/2”: 3 ft2 and or 6 lbs. of metal
- Sodium Potassium Alloy Spill: 3 ft2 and/or 2 lbs. of metal

**MODEL B571** contains a copper extinguishing agent specially developed by the U.S. Navy for fighting lithium and lithium alloy fires. The copper compound smothers the fire and provides an excellent heat sink for dissipating heat. Copper powder has been found to be superior to all other known fire extinguishing agents for lithium.

Extinguishing Capacity - 4 ft2 and/or 5 lbs. of lithium

SPECIFICATIONS		
Model Number	B570	B571
Agent	Sodium Chloride	Copper
Application	Hose & Wand Applicator	
Capacity	13.6 Kg	13.6 Kg
Shipping Wt (Empty)	24.1 Kg	24.1 Kg
Height mm	900	600
Width mm	330	330
Depth mm	200	200
Range m	1 - 2	1 - 2
Discharge time Sec	24	18
FM Approved	Yes	Yes
Standard Bracket	Wall Bracket	

For more information contact :

**FIRE SAFETY EQUIPMENT**

[www.fsequip.com.au](http://www.fsequip.com.au)

Sydney - Brisbane - Auckland

