



Quality is Behind the Diamond®  
**Amerex Corporation**

Manufactured to  
 ANSI / UL Standards  
 AS & NZ Standards  
 ISO-9001 / ISO-14001 Certified

**RUGGED**

- High Grade Stainless Steel Cylinders
- Stored Pressure design
- All Metal Valve Construction
- UV Rated Powder Coating
- Easy to Service and Maintain
- UL Listed
- Coast Guard Approved
- Temperature Range -53°C to 50°C
- Bar Coded Labels
- Leaves no powder residue



WATER & FOAM

**Model 240** utilises the cooling, soaking and penetrating effect of a 13-17m stream of WATER. The 60 sec. discharge time makes it very effective for inexperienced operators to use on Class A fires. Protect from Freezing by adding the Model 506 Stream/Anti Freeze charge. In Western Australia, South Australia and other areas with a high level of chloride content water it must be corrosion protected by adding the Model 507 charge.

**Model 250 AFFF FOAM** Class A:B extinguisher. Easy and effective application with air asperated nozzle. Apply to Class B liquid spills to prevent ignition. Ideal for emergency first response vehicles.

**Model 252 FFFP FOAM** adds Class B fire fighting capacity to the Class A effectiveness of this extinguisher. The Alcohol Resistant fire fighting Agnet is effective on a wide variety of Class B materials such as alcohols, polar solvents, hydrocarbons, and combinations such as gasohol. Apply to non-ignited Class B liquid spill and it will seal the surface minimising their chance of serious fire.

**Model 254 AFFF FOAM** unique 6 litre size fills many requirements for alighter, more compact Class A:B Extinguisher. Easy and effective application with the patented Spray nozzle. Apply to Class B liquid spills to prevent ignition, Ideal for emergency first response vehicles.

SPECIFICATIONS	Water	AFFF Foam		FFFP Foam
Model Number	240AS	250AS	254	252
Application	Hose and Nozzle	Hose & Air Aspirated Nozzle	Hose & Spray Nozzle	Hose & Air Aspirated Nozzle
U.L. Rating	2A	3A:20B	2A:10B	3A:20B
AS/NZ Rating	3A	3A:20B	-	-
SSL Listed	Yes	Yes	-	-
FM Approved	Yes	Yes	-	-
Capacity	9.1 Litres	9.1 Litres	6 Litres	9 Litres
Shipping Wt (Empty)	3.4 Kg	5 Kg	3.6 Kg	5 Kg
Height mm	620	620	485	620
Width mm	230	230	200	230
Depth mm	180	180	180	180
Range m	13-17	3-4	3-4	3-4
Discharge time Sec	60	55	60	60-65
Standard Bracket	Wall Bracket			